

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : PU MATCOAT - B COMP.  
Type of product : Hardener (Crosslinker)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Rewah  
Nijverheidsweg 24  
B-2240 Zandhoven - Belgique-België  
T +32 (0)3 4751414 - F +32 (0)3 4751094  
[info@rewah.com](mailto:info@rewah.com)

#### 1.4. Emergency telephone number

Emergency number : +32 (0)70 245 245

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Sens. 1 H317  
STOT SE 3 H335  
Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Harmful if inhaled. May cause respiratory irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning  
Hazardous ingredients : Hexamethyleen-diisocyanat polymer; aliphatic polyisocyanate resin; hexamethylene-diisocyanate  
Hazard statements (CLP) : H317 - May cause an allergic skin reaction.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.  
P273 - Avoid release to the environment.  
P280 - Wear Protective gloves, protective clothing, eye protection, face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P501 - Dispose of contents/container to Collection point.

# PU MATCOAT - B COMP.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### 2.3. Other hazards

Other hazards not contributing to the classification : The product does not meet the PBT and vPvB classification criteria.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hexamethylen-diisocyanat polymer	(CAS-No.) 28182-81-2 (REACH-no) 01-2119485796-17	25 - 90	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
aliphatic polyisocyanate resin	(CAS-No.) 160994-68-3	5 - 25	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
hexamethylene-di-isocyanate	(CAS-No.) 822-06-0 (EC-No.) 212-485-8 (EC Index-No.) 615-011-00-1	0.1 - 0.3	Acute Tox. 1 (Inhalation), H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
hexamethylene-di-isocyanate	(CAS-No.) 822-06-0 (EC-No.) 212-485-8 (EC Index-No.) 615-011-00-1	(C >= 0.5) Skin Sens. 1, H317 (C >= 0.5) Resp. Sens. 1, H334

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: No hazards which require special first aid measures. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Not required.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray.

### 5.2. Special hazards arising from the substance or mixture

Explosion hazard	: Not applicable.
Reactivity in case of fire	: Not applicable.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

# PU MATCOAT - B COMP.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### 5.3. Advice for firefighters

- Precautionary measures fire : Avoid (reject) fire-fighting water to enter environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : High temperature may liberate toxic gases. In case of fire: keep cylinder cool by spraying with water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable protective clothing, gloves and eye/face protection.
- Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Restrict liquid from spreading over surface with floating screens if possible.

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Clean up any spills as soon as possible, using an absorbent material to collect it. Waste to eliminate according to chemical waste law.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Store in tightly closed packings.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Storage temperature : 5 - 30 °C

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

hexamethylene-di-isocyanate (822-06-0)		
Belgium	Local name	Diisocyanate d'hexaméthylène
Belgium	Limit value (mg/m³)	0.034 mg/m³
Belgium	Limit value (ppm)	0.005 ppm

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Materials for protective clothing:

Wear suitable protective work clothes.

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Nitrile rubber gloves. Butylrubber protective gloves. VITON gloves

#### Eye protection:

Safety goggles recommended during refilling

#### Skin and body protection:

If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Avoid contact with skin.

# PU MATCOAT - B COMP.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. During spraying wear suitable respiratory equipment.

### Environmental exposure controls:

Product may not flow into sewer or superficial water. Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: yellowish.
Odour	: Almost odorless.
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: < 30 °C Not applicable
Freezing point	: No data available
Boiling point	: > 300 °C
Flash point	: 184 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: < 0.0001 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Material insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 1400 mPa·s
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

To avoid thermal decomposition, do not overheat.

### 10.3. Possibility of hazardous reactions

Reacts with : Water. alcohols. amines. acids. An exothermic reaction may occur.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:dust,mist: Harmful if inhaled.

#### Hexamethylen-diisocyanat polymer (28182-81-2)

LD50 oral rat	746 mg/kg
---------------	-----------

# PU MATCOAT - B COMP.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Hexamethylen-diisocyanat polymer (28182-81-2)	
LD50 dermal rabbit	> 7000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	0.124 mg/l/4h
aliphatic polyisocyanate resin (160994-68-3)	
LD50 oral rat	> 2000 mg/kg
hexamethylene-di-isocyanate (822-06-0)	
LD50 oral rat	746 mg/kg
LD50 dermal rabbit	> 7000
LC50 inhalation rat (Dust/Mist - mg/l/4h)	0.124 mg/l/4h
Skin corrosion/irritation	: Not classified pH: Not applicable.
Serious eye damage/irritation	: Not classified pH: Not applicable.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

PU MATCOAT - B COMP.	
Viscosity, kinematic	1217.39130435 mm <sup>2</sup> /s

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : In water, material soluble. Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

aliphatic polyisocyanate resin (160994-68-3)	
LC50 fish 1	23.8 mg/l Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 100 mg/l
hexamethylene-di-isocyanate (822-06-0)	
LC50 fish 1	82.8 Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 89.1 mg/l
EC50 72h algae (1)	> 77.4 mg/l

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

PU MATCOAT - B COMP.	
Ecology - soil	None known.

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

# PU MATCOAT - B COMP.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Regional legislation (waste) : Forbidden through garbage can or sewerage, follow the next guidelines: 75/442/EG & 91/689/EG .
- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with ADR / IATA

#### 14.1. UN number

- UN-No. (ADR) : Not applicable
- UN-No. (IATA) : Not applicable

#### 14.2. UN proper shipping name

- Proper Shipping Name (ADR) : Not applicable
- Proper Shipping Name (IATA) : Not applicable

#### 14.3. Transport hazard class(es)

##### ADR

- Transport hazard class(es) (ADR) : Not applicable

##### IATA

- Transport hazard class(es) (IATA) : Not applicable

#### 14.4. Packing group

- Packing group (ADR) : Not applicable
- Packing group (IATA) : Not applicable

#### 14.5. Environmental hazards

- Dangerous for the environment : No
- Other information : No supplementary information available

#### 14.6. Special precautions for user

##### - Overland transport

Not applicable

##### - Air transport

Not applicable

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

- Contains no REACH substances with Annex XVII restrictions
- Contains no substance on the REACH candidate list
- Contains no REACH Annex XIV substances

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

- Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

# PU MATCOAT - B COMP.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 1 (Inhalation)	Acute toxicity (inhal.), Category 1
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
Aquatic Chronic 3	H412	Calculation method

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*